



THE FLEXIBLE OPS-READY MONITOR

Ready for Everything

Meet the world's first desktop display featuring an integrated Open Pluggable Specification slot.

Designed for use in education, business, and government, transform desktop computing into a cable-free AIO by sliding in any Windows, Android, or ChromeOS OPS device. Eliminate cable clutter, simplify fleet management, and future-proof your hardware investment with this platform-agnostic, budget-friendly solution, all backed by CTL's proven technology lifecycle service expertise.

Create an all-in-one desktop solution that fits your needs.

Seamlessly pairs with any standard Windows, Android, or ChromeOS OPS device—including the CTL Chromebox OPS—to create a modular, cable-free AIO solution.

Future-proof your desktops.

Upgrading computing power requires swapping only the internal OPS module, preserving the monitor hardware and extending your technology investment.

Reduce deployment time and simplify clutter complexity.


Simplify deployment to a single power cord and reduce "loose cable" helpdesk tickets in high-traffic environments.

Simplified, budget-friendly IT management.

Streamline your fleet and standardize your maintenance. Dramatically reduce your spare parts inventory and perform near-instantaneous computer module swaps without disconnecting cables or unmounting monitors.

CTL: your technology lifecycle partner.

Over the years we've built expertise, systems, and customer-support processes that get you up and running quickly and smoothly.



CTL OPS-Ready Monitor Specifications

Deliver a smarter, more flexible all-in-one desktop solution.

The CTL 24" MTIP24OPS OPS-Ready Monitor is a platform-agnostic, full HD (1920 x 1028) desktop display that serves as the foundation for a cable-free AIO desktop computing system

Specifications	CTL OPS-Ready Monitor
Case type	All-in-One
Display	23.8" LED Full HD 1920 × 1080 pixels 3 sides borderless panel
Contrast ratio	1000
Response time	14-20 ms
Platform	None - requires OPS device
Webcam	Built-in 5 MP webcam, +/- 20 degree mechanical angle adjustment
Speakers	2 × 3W
Fan	50:15 mm blower
Connection ports	Side I/O: USB 2.0 Type-A x 2, USB 3.0 Type-A x 1, USB 3.0 Type-C x 1 Rear panel: 1 x HDMI-IN
Stand	Height adjustable stand, with specs: Traveling distance: 130 mm Tilt angle -5 to 25 degrees Swivel angle: 350 degrees Pivot angle: 0-90 degrees
Brightness	250 cd/m2
Panel dimensions	Without stand: 12.64" h x 21.30" w x 2.32" d, 321 × 541 × 59 mm
VESA mount capable	100×100 mm
Power	Internal adaptor 12 V / 150 W
Weight	12.57 lbs., 5.7 kg without OPS unit installed
Compliance	This product is CE marked, TÜV certified, and FCC compliant.



CTL - Your Technology Lifecycle Partner

For tech leaders stretched thin, CTL is more than a vendor—we're your strategic technology lifecycle partner. CTL replaces transactional vendors with a side-by-side partnership, delivering the most complete set of award-winning product and service solutions that streamline the entire technology lifecycle. CTL is a Certified B Corp™ for our commitment to sustainability and social responsibility.